

## ZELL-FAST 1.7 (ZF 1.7) SPECIFICATIONS

# BASE SHEET TO LIGHTWEIGHT INSULATING CONCRETE

### COMPOSITION

Fastener: Precision formed from polymer coated steel to prevent corrosion. Rectangular dual gripping legs, 1.7" long.

**Disk**: Precision formed from coated steel to prevent corrosion. Integrally locked to fastener. Rib reinforced cap, 2.7" diameter.

#### TECHNICAL DATA

Approvals: ZF1.7 fasteners maintain Factory Mutual, Underwriters Lab Approvals, and Miami-Dade County Approvals.

Fastening Pattern: Consult Factory Mutual, Underwriters Lab, or Miami-Dade requirements for recommended pattern in normal, exposed, and hurricane areas.

Field Testing: On-site withdrawal testing should always be performed to evaluate the ability of the roofing substrate to satisfactorily accept and retain fasteners. Such testing may alter fastener selection and modify applicable fastening patterns.

#### INSTALLATION

Equipment: Always use the Zell Magnetic Driver to assure proper fastener installation.

Method: Drive ZF1.7 as an ordinary nail. DO NOT TOE. Seat cap flush with roofing surface (see illustration).

Operation: As ZF1.7 is driven, dual legs diverge and cut a plug of deck material that wedge and anchor the ZF1.7 in its own hole. No pre-drilling is required.


Availability: ZF1.7 is a proprietary product manufactured only by ES Products, Inc. and distributed by leading roofing material and equipment wholesalers throughout the United States.


Packaging: 1,000 ZF1.7 fasteners per carton. Gross weight: 40 lbs. Shrink wrapped and palletized.

#### **USING THE ZF 1.7**

Fastener density and spacing vary depending on applicable uplift requirements. Local codes, governing approval bodies and membrane manufacturers all may have specific requirements that need to be addressed prior to beginning any roofing project. Contact the roof-membrane manufacturer for approved fastening pattern.

Warranty: ES Products, LLC warrants its products for one year from date of sale against defective workmanship and material, and its liability therefore shall be limited to replacing defective products reported defective during the warranty period. ES Products is not responsible for any failure attributable to improper use or installation in any manner inconsistent with manufacturer's specifications. THIS WARRANTY IS IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, ALL OF WHICH ARE EXPRESSLY DISCLAIMED INCLUDING ANY WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR PARTICULAR USE. This warranty provides specific legal rights and remedies that may vary from state to state.





Fastener anchors itself in its own hole by cutting an inverted wedge of concrete. No pre-drilling required.





